

CARACTERÍSTICAS TÉCNICAS / TECHNICAL FEATURES

INCH	1	1 ¼	1 ½	2	2 ½	3	4	5	6	8	10	12	16
Ø(mm)	32	40	50	63	75	90	110	125	160	200	250	315	400
Min m³/h	0.7	1	2	3	4	6	9	12	19	30	47	75	122
Min gpm	3	5	8	12.4	18	25	38	49	80	125	196	311	540
K-factor (pulse/liter)	57	30	18.6	15.6	12.3	7.6	5.3	4.0	2.0	1.4	0.8	0.4	0.2
K-factor (pulse/galon)	214	113	71.5	59	47	29	20	15.1	7.7	5.2	3.0	1.6	0.9



Rango de velocidad / Flow rate range: 0.3-6 m/s / 0.9-20 ft/s

Voltaje alimentación / Input Voltage: 3.3-24 V DC

Señal de salida / Output Signal: Frecuencia (colector abierto) / Frequency (open collector): 35 Hz por m/s

Longitud del cable / Cable length: 7.6 m / 25 ft.





Presión máxima / Max pressure: 12,5 bar @ 20°C / 180 psi - 68°F

Material: P.V.D.F.


Protección / Protection: IP67

Conexión / Wiring:

1. Rojo / Red +
2. Negro / Black -
3. Blanco / White -




COMPACT PVC FITTING




INCH:	1/2	3/4	1	1 1/4
Ø(mm):	20	25	32	40
Ref:	20-014	20-015	20-016	20-017

ADAPTADOR PARA SOLDAR / WELD-ON ADAPTER



INCH:	8	10	12	316	20
Ø(mm):	200	250	315	400	500
Ref:	20-162			20-163	

COLLARIN DE TOMA / SADDLE CLAMP



INCH:	1 ½	2	2 ½	3	4	5	6	8	10	12	
Ø(mm):	50	63	75	90	110	125	140	160	200	250	315
Ref:	20-040	20-041	20-042	20-043	20-044	20-045	20-046	20-047	20-158	20-159	20-160